

Winterization / De-Winterization

Winterizing Sunseeker 3170DS

1. Purchase 4-6 gallons of RV approved, non-toxic antifreeze.
2. Drain all tanks (fresh water and sewage tanks). Fresh water tank drain is located in the second compartment from the rear of the vehicle on the passenger side. Open up the basement storage door, inside there is another door straight ahead. Locate the blue plastic pipe with a valve on it. Open the valve and allow the water to begin to drain.
3. Turn water heater bypass valve to bypass position. (Located Under the main cabin sink behind the drawers)
4. Drain water heater by removing the drain valve (2016 Sunseeker) or anode rod (2014 Sunseeker). Allow the water to drain. Do not replace the plug / anode rod, leave open.
5. The 2014 Sunseeker has a water filtration system installed. Remove the water filter from the enclosed casing and then put the plastic casing back on. Only loosen and tighten by hand.
6. Turn on the water tank bypass on so you can place the hose in the antifreeze.
7. Turn the pump switch 'ON' (Above fridge) and open the cold water side of all faucet fixtures. Leave the faucets open until the antifreeze (generally pink in color) flows out of the faucets. Repeat for the hot water side. Don't forget to repeat these steps for each:
 - Kitchen Sink
 - Bathroom Sink
 - Shower
 - Outside Shower
8. Flush toilet until antifreeze is visible inside the bowl and pour one gallon of antifreeze down the toilet to winterize the black holding tank.
9. Pour antifreeze in the shower/tub, lavatory sink and kitchen sink to fill p-traps.
10. To winterize gray tank(s), pour one gallon down each related sink drain.

NOTE:

Do not attempt to turn on the water heater or use the plumbing system once the system has been winterized. Dewinterize the water system, flush and sanitize prior to use.



Dewinterizing Sunseeker 3170DS

1. Drain all holding tanks (fresh water and sewage).
2. Attach specially designed water hose to city hookup input and run a sink. **(DO NOT TURN ON WATER PUMP WHEN CONNECTED TO CITY HOOKUP)**
3. Attach specially designed water hose to fresh water input and fill tank.
4. Turn 'ON' pump switch and open cold water side of all faucet/shower fixtures. Leave open until the water runs clear (no pink residue). Repeat for the hot water side.
5. Flush toilet until clear water runs into bowl.
6. Dump tanks again.
7. Sanitize the water system.
8. Replace the missing water filter. Fresh water tank filter (Sunseeker 2014) is located in the second compartment from the rear of the vehicle on the passenger side. Open up the basement storage door, inside there is another door straight ahead.
9. Replace the hot water tank plug (2016 Sunseeker) or anode rod (2014 Sunseeker) in the tank. This is located in the panel about the middle of the unit on the driver side of the RV.
10. Turn the hot water tank bypass valve to the open position to allow water to fill the hot water tank.

