

Winterization / De-Winterization

Winterizing Sunseeker 3170DS

1. Purchase 4-6 gallons of RV approved, non-toxic antifreeze.
2. Drain all tanks (fresh water and sewage tanks). Fresh water tank drain is located in the second compartment from the rear of the vehicle on the passenger side. Open up the basement storage door, inside there is another door straight ahead. Locate the blue plastic pipe with a valve on it. Open the valve and allow the water to begin to drain.
3. Turn water heater bypass valve to bypass position. (Located Under the main cabin sink behind the drawers)
4. Drain water heater by removing the white nylon / plastic drain valve. Allow the water to drain. Do not replace the plug, please put it in the glove box
5. The Sunseeker has a water filtration system installed. Remove the water filter from the enclosed casing and then put the plastic casing back on. Only loosen and tighten by hand.
6. Turn on the water tank bypass and place the hose in the bottle of antifreeze.
7. Go inside and turn the pump switch 'ON' (Above fridge) and open the cold-water side of all faucet fixtures (One at a time). Leave the faucets open until the antifreeze (generally pink in color) flows out of the faucet. Repeat for the hot water side. Don't forget to repeat these steps for each:
 - Kitchen Sink
 - Bathroom Sink
 - Shower
 - Toilet
 - Outside Shower
8. Flush toilet until antifreeze is visible inside the bowl and pour one gallon of antifreeze down the toilet to winterize the black holding tank.
9. Pour antifreeze in the shower/tub, lavatory sink and kitchen sink to fill p-traps.

NOTE:

Do not attempt to turn on the water heater or use the plumbing system once the system has been winterized. Dewinterize the water system, flush and sanitize prior to use.



De-winterizing Sunseeker 3170DS

1. Most likely the fresh-water tank valve is open, make sure it is closed. This is located next to the water pump in the second compartment from the rear (passenger side).
2. Flush lines by either:
 1. Fill the fresh-water tank with water, and turn the water pump on (Located above the fridge) or
 2. Attached fresh-water hose to "City Water Hookup"
3. Run each until the water runs clear:
 - Kitchen Sink
 - Bathroom Sink
 - Shower
 - Toilet
 - Outside Shower
4. Put the hot water tank plug bank in. This should be found in the glove-box. This is located in the panel about the middle of the unit on the driver side of the RV.
5. Turn the hot water tank bypass valves to the open position to allow water to fill the hot water tank.
 1. You will have to remove the second drawer under the kitchen sink to get to the valves.

Below is an image of the Hot Water Tank Plug (Left) and the adapter to allow you to clear the water lines using a compressor (Right)



Fresh water by-pass (White on left)

Water Drain (Blue in middle)

Water Filter (Right, filled with Pink solution). **Note: This does NOT have to run with a filter in it. It can be run without the water filter. Only HAND TIGHTEN.**



Below is an image of the hot water tank by-pass levers. This is located under the kitchen sink. To access these levers you must remove the second drawer (From the top).

THE SETTINGS SHOWN ARE THAT OF THE BYPASS BEING TURNED ON (Winterized). Water (IE Pink Solution) is currently NOT flowing into the hot water tank.

